


2 inch ALTAZIMUTH REFRACTOR



ADDITIONAL EYEPIECE AVAILABLE—

Prod. No. 16630 18mm Kellner (for 39x)
Prod. No. 16631 12.5mm Kellner (for 56x)
Prod. No. 16634 7mm Ach. Sym. (for 100x)
Prod. No. 16635 6mm Orthoscopic (for 117x)
Prod. No. 16637 4mm Orthoscopic (for 175x)

ADDITIONAL ACCESSORIES AVAILABLE—

Prod. No. 16624 Model A UNIHEX Prod. No. 16643 Erecting Prism MODEL 105—Complete with Altazimuth Mount with slow motion controls for both altitude and azimuth, sturdy wood tripod with folding legs and leg brace, 4x-19mm viewfinder with crossline eyepiece, rack and pinion focusing mechanism with drawtube, star diagonal, 2 coated eyepieces; 9mm (78x) and 25mm (28x), dustcap, instruction manual.

Prod. No. 16650 Model 105 2" Altazimuth Refractor



SPECIFICATIONS

Unitron Model 105 2" Altazimuth Refractor

1. DIMENSIONS:

Length of optical system (eyepiece to dustcap)	26"
Height of instrument (ground to clamp)	54"

2. WEIGHT:

Shipping weight	15 lbs.
Instrument in observing position	9 lbs.

3. ALTITUDE & AZIMUTH TRAVEL:

	Fast Motion	Slow Motion	Angular travel/revolution of slow motion control knob
Altitude	180°	22° 00′	1°
Azimuth	360°	31° 30′	0° 30′

4. OBJECTIVE:

Achromatic, air-spaced, coated, 2-element 50mm clear aperture, 700mm focal length, f/14, resolving power 2.3 arcsec, minimum magnitude observable + 10.5, field of view 7° 12 '.

5. VIEWFINDER:

Focusable 4X eyepiece with crossline, 19mm objective, field of view 7° 12'.

6. TABLE OF MAGNIFICATIONS: (Objective focal length ÷ Eyepiece focal length)

Eyepiece Focal Length	Magnification†	Field of View
04mm	175X	0° 14′
05mm	140	0° 18′
06mm	117	0° 21′
AS7mm	100	0° 23′
AS9*mm	78	0° 29′
K12.5mm	56	0°38′
K18mm	39	0° 1.9′
R25*mm	28	0° 26′

^{*} Supplied as standard equipment.

7. WARRANTY: Full 25-year warranty. Written warranty can be obtained free of charge upon specific written request, at the address shown below.